

# Ka-98H

**iNetVu**<sup>®</sup>  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu<sup>®</sup> Ka-98H Drive-Away Antenna is a 98 cm auto-acquire satellite antenna system which can be mounted on the roof of a vehicle for Broadband Internet Access over any configured satellite. The system works seamlessly with the iNetVu<sup>®</sup> 7024C Controller providing fast satellite acquisition within minutes, anytime anywhere.



**“Suitable to operate over the Yahsat’s Yahclick network”**

### Features

- One-Piece high surface accuracy, offset feed, steel reflector
- Heavy duty feed arm capable of supporting up to 5kg (10 lbs) RF Electronics (LNB & BUC) or transceiver
- Designed to work with the iNetVu<sup>®</sup> 7024C Controller
- Works seamlessly with the world’s most popular commercially available Ka modems and services
- 2 Axis motorization/ 3 Axis optional (Jupiter only)
- Supports manual control when required
- One button, auto-pointing controller acquires any Ka-band satellite within 2 minutes
- Field upgradable to Ku-band
- Locates satellites using the most advanced satellite acquisition methods
- Supports Skyware Global 98 cm Ka antenna
- Works with HNS Spaceway (NA)<sup>(1)</sup>, YAHSAT (MENA)<sup>(1)</sup> and Avanti approved<sup>(1)</sup>
- Available with pod option
- Standard 2 year warranty

avanti **Approved  
Compatibility**

### Application Versatility

If you operate in Ka-band, the Ka-98H system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

Notes:

<sup>(1)</sup> Supported Radios: Spaceway or Jupiter. Please specify which radio being used when ordering.  
<http://www.avantiplc.com/avanti-approved-compatibility>

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)  
[www.c-comsat.com](http://www.c-comsat.com)

Specifications are subject to change

Aug 2015

# Ka-98H

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

### Mechanical

Reflector	98 cm Elliptical Antenna, Offset feed
Platform Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass ± 2° Tilt sensor ± 0.1
Azimuth	Full 360° in overlapping 200° sectors
Elevation	0 - 90°
Elevation Deploy Speed	Variable 2°/sec typ.
Azimuth Deploy Speed	Variable 15°/sec Max., 10°/sec typ.
Peaking Speed	0.1°/sec

### Environmental

Survival	
Wind Deployed	160 km/h (100 mph)
Wind Stowed	225 km/h (140 mph)
Temperature	-40°C to 65°C (-40°F to 150°F)
Operational	
Wind	72 km/h (45 mph)
Temperature	-30°C to 55°C (-22°F to 130°F)

Thermal Test per MIL-STD-810F, Method 501.4, High/Low Temperatures  
Vibration Test per MIL-STD-810F, Annex A, Category 4, Truck/Trailer/Tracked  
Shock Test per IEC 60068-2-27, Water Ingress per IP-66

### Electrical

Rx & Tx Cables	2 RG6 cables - 10 m (33 ft) each	
Control Cables		
Standard	10 m (33 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
Frequency (GHz)	<b>Receive</b> 19.20 - 20.20	<b>Transmit</b> 29.50 - 30.00
Feed Interface (Circular)	RG6	RG6
Midband Gain (± 0.2 dBi)	43.50 @19.75 GHz	46.60 @29.75GHz
Antenna Noise Temp. (K)	30° EL= 62 Max.	
Sidelobe Envelope, Co-Pol (dBi)		
100λ / D < Ø < 20°	29 - 25 Log Ø	
20° < Ø < 26.3°	-3.5	
26.3° < Ø < 48°	32-25 Log Ø	
48° < Ø < 180°	-10 (typical)	
Cross-Polarization	> -24 dB	> -22 dB
VSWR	1.3:1	

### RF Interface

Radio Mounting	Feed Arm <sup>(1)</sup>
Coaxial	RG6U from Transceiver to Base Connector

### Physical

Mounting Plate	L: 161 cm (63.5")	W: 45 cm (17.7")
Stowed Reflector Ext. Dims (without reflector pod)	L: 164.8 cm (64.9")	W: 100 cm (39.5")
H: 30 cm (11.8")		
Stowed Reflector Ext. Dims (with reflector pod)	L: 178.8 cm (70.4")	W: 113 cm (44.5")
H: 30 cm (11.8")		
Deployed Height	151 cm (59.5")	
Platform Weight	54 kg (119 lbs)	
Reflector back cover	2.27 kg (5 lbs)	
Pod alone	6.8 kg (15 lbs)	
Total Platform Weight (without reflector pod)	56.3 kg (124 lbs)	
Total Platform Weight (with reflector pod)	63 kg (139 lbs)	

### Motors

Electrical Interface	24VDC	8 Amp (Max.)
----------------------	-------	--------------

### Shipping Weights & Dimensions\*

Crate: 183 cm x 109 cm x 66 cm (72" x 43" x 26"), 52 kg (115 lbs)  
Platform: 54 kg (119 lbs)  
7024C Controller: 6 kg (13 lbs)  
Cables: 5 kg (11 lbs)

Total weight: 117 kg (258 lbs)

Transportable Case Option:

Base Case: 183 cm x 109 cm x 47 cm (72" x 43" x 18.5"), 133.5 kg (294 lbs)

\*The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

Notes:

<sup>(1)</sup> Supported Radios: Spaceway or Jupiter

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)

www.c-comsat.com

**C-COM**  
SATELLITE SYSTEMS INC.

Specifications are subject to change

Aug 2015